

HM Wire International, Inc.

Ph: 330-244-8501 Fax: 330-244-8561

www.litz-wire.com info@litz-wire.com www.hmwire.com



Stainless Steel Cable, FEP® Coated

Construction is the same for both Uncoated and Nylon Coated dimensions

Part No.	Uncoated Nominal Diameter		Construction	Minimum Breaking Strength		Outside Coating Diameter		Approximate Weight per 100 ft.	
	in.	mm		lbs	kgs	in.	mm	lbs	kgs
HM14ST	0.14	0.356	7x7	26	12	0.021	0.53	0.04	0.02
HM18ST	0.18	0.457	7x7	40	18	0.026	0.66	0.06	0.03
HM23ST	0.24	0.610	7x7	70	32	0.032	0.813	0.14	0.06
HM24ST	0.24	0.610	7x19	70	32	0.032	0.813	0.14	0.06
HM27ST	0.27	0.686	7x7	90	41	0.036	0.914	0.15	0.07
HM31ST	0.32	0.813	7x7	120	54	0.040	1.02	0.22	0.10
HM32ST	0.32	0.813	7x19	120	54	0.040	1.02	0.22	0.10
HM36ST	0.36	0.914	7x7	160	73	0.049	1.24	0.26	0.12
HM37ST	0.38	0.914	7x19	160	73	0.049	1.24	0.26	0.12
HM48ST	3/64	1.19	7x7	270	122	0.062	1.59	0.49	0.22
HM50ST	3/64	1.19	7x19	270	122	0.062	1.59	0.49	0.22
HM54ST	0.54	1.37	7x49	250	113	0.062	1.59	0.65	0.29
HM64ST	1/16	1.59	7x7	480	218	0.084	2.13	0.85	0.39
HM65ST	1/16	1.59	7x19	480	218	0.084	2.13	0.85	0.39
HM95ST	3/32	2.38	7x19	920	417	1/8	3.18	2.25	1.02
HM126ST	1/8	3.18	7x19	1760	798	3/16	4.76	4.35	1.98
HM188ST	3/16	4.76	7x19	3700	1678	1/4	6.35	9.60	4.36

To be used as a Guideline ONLY!

Copyright ©2012 HM Wire International Inc.

R1. 7/24/2012