

HM Wire International, Inc.
 Ph: 330-244-8501 Fax: 330-244-8561
 www.litz-wire.com info@litz-wire.com www.hmwire.com



Low-Stretch High Fatigue Miniature and Small Cables

Stainless Steel Cable, Nylon Coated

Uncoated						With Nylon Coating			Approx. Weight per 100 ft.			
Part No.	Nominal Diameter		Constru- ction	Min. Breaking Strength		Part No.	Coating Diameter		Uncoated		Coated	
	in.	mm		lbs	kgs		in.	mm	lbs	kgs	lbs	kgs
HMHF1	0.021	0.534	7x7	50	22.7	HMHF1SN	0.027	0.686	0.11	0	0.12	0.05
HMHF2	0.024	0.610	7x7	70	31.8	HMHF2SN	0.030	0.762	0.12	0.05	0.14	0.06
HMHF3	0.024	0.610	7x19	60	27.2	HMHF3SN	0.030	0.762	0.12	0.05	0.14	0.06
HMHF4	0.027	0.686	7x7	90	40.8	HMHF4SN	0.034	0.864	0.13	0.06	0.15	0.07
HMHF5	0.032	0.813	7x7	120	54.4	HMHF5SN	0.037	0.940	0.16	0.07	0.22	0.10
HMHF6	0.032	0.813	7x19	100	45.4	HMHF6SN	0.037	0.940	0.16	0.07	0.22	0.10
HMHF7	0.036	0.914	7x7	160	72.6	HMHF7SN	0.046	1.17	0.23	0.10	0.26	0.12
HMHF8	0.036	0.914	7x19	150	68.0	HMHF8SN	0.046	1.17	0.23	0.10	0.26	0.12
HMHF9	0.048	1.19	7x7	270	122.5	HMHF9SN	0.063	1.59	0.42	0.19	0.49	0.22
HMHF10	0.048	1.19	7x19	270	122.5	HMHF10SN	0.063	1.59	0.55	0.25	0.65	0.29
HMHF11	0.063	1.59	7x7	450	204.1	HMHF11SN	0.094	2.38	0.75	0.34	0.93	0.42
HMHF12	0.063	1.59	7x19	450	204.1	HMHF12SN	0.094	2.38	0.75	0.34	0.93	0.42

To be used as a Guideline ONLY!

Copyright ©2012 HM Wire International Inc.

R1. 7/20/2012