

**HM Wire International, Inc.**  
 Ph: 330-244-8501 Fax: 330-244-8561  
 www.litz-wire.com info@litz-wire.com www.hmwire.com



## Precision Miniature and Small Cables

Stainless Steel Cable, Nylon Coated

Uncoated						With Nylon Coating			Approx. Weight per 100 ft.			
Part No.	Nominal Diameter		Constru- ction	Min. Breaking Strength		Part No.	Coating Diameter		Uncoated		Coated	
	in.	mm		lbs	kgs		in.	mm	lbs	kgs	lbs	kgs
HM006	0.006	0.152	1x7	5	2.3	HM006SN	0.010	0.254	0.01	0	0.01	0
HM009	0.009	0.229	3x7	10	4.5	HM009SN	0.014	0.356	0.02	0.01	0.02	0.01
HM010	0.010	0.254	7x7	15	6.8	HM010SN	0.014	0.356	0.02	0.01	0.02	0.01
HM011	0.012	0.305	1x7	20	9.1	HM011SN	0.019	0.483	0.03	0.01	0.04	0.02
HM012	0.013	0.305	3x7	18	8.2	HM012SN	0.019	0.483	0.03	0.01	0.04	0.02
HM014	0.014	0.356	7x7	26	11.8	HM014SN	0.019	0.483	0.03	0.01	0.04	0.02
HM015	0.016	0.406	1x7	30	13.6	HM015SN	0.024	0.610	0.04	0.02	0.05	0.02
HM016	0.017	0.432	3x3	26	11.8	HM016SN			0.04	0.02		
HM017	0.019	0.483	1x7	40	18.1	HM017SN	0.024	0.610	0.06	0.03	0.07	0.03
HM018	0.018	0.457	7x7	40	18.1	HM018SN	0.024	0.610	0.05	0.02	0.06	0.03
HM019	0.018	0.457	7x19	40	18.1	HM019SN	0.024	0.610	0.05	0.02	0.06	0.03
HM020	0.018	0.457	1x19	45	20.5	HM020SN			0.05	0.02		
HM023	0.024	0.610	7x7	70	31.8	HM023SN	0.030	0.762	0.12	0.05	0.14	0.06
HM024	0.024	0.610	7x19	70	31.8	HM024SN	0.030	0.762	0.12	0.05	0.14	0.06
HM027	0.027	0.686	7x7	90	40.8	HM027SN	0.034	0.864	0.13	0.06	0.15	0.07
HM030	0.032	0.813	3x7	110	49.9	HM030SN	0.037	0.940	0.16	0.07	0.22	0.10
HM031	0.032	0.813	7x7	120	54.4	HM031SN	0.037	0.940	0.16	0.07	0.22	0.10
HM032	0.032	0.813	7x19	120	54.4	HM032SN	0.037	0.940	0.16	0.07	0.22	0.10
HM033	0.032	0.813	7x49	100	45.4	HM033SN	0.037	0.940	0.16	0.07	0.22	0.10
HM035	0.036	0.914	3x49	120	54.4	HM035SN	0.044	1.12	0.23	0.10	0.24	0.11
HM036	0.035	0.914	7x7	160	72.6	HM036SN	0.044	1.12	0.23	0.10	0.26	0.12
HM037	0.038	0.965	7x19	160	72.6	HM037SN	0.046	1.17	0.23	0.10	0.26	0.12

**HM Wire International, Inc.**  
 Ph: 330-244-8501 Fax: 330-244-8561  
 www.litz-wire.com info@litz-wire.com www.hmwire.com



## Precision Miniature and Small Cables

### Stainless Steel Cable, Nylon Coated

Uncoated						With Nylon Coating			Approx. Weight per 100 ft.			
Part No.	Nominal Diameter		Constru- ction	Min. Breaking Strength		Part No.	Coating Diameter		Uncoated		Coated	
	in.	mm		lbs	kgs		in.	mm	lbs	kgs	lbs	kgs
HM038	0.038	0.965	49+(8x19)	160	72.6	HM038SN	0.046	1.17	0.23	0.10	0.26	0.12
HM039	0.038	0.965	1x19	160	72.6	HM039SN	0.046	1.17	0.23	0.10	0.26	0.12
HM045	0.044	1.12	7x19	220	100	HM045SN	0.052	1.32	0.35	0.16	0.39	0.18
HM046	0.046	1.17	7x7	225	100	HM046SN	0.052	1.32	0.37	0.17	0.41	0.19
HM047	0.044	1.12	7x49	170	77.1	HM047SN	0.052	1.32	0.35	0.16	0.39	0.18
HM048	3/64	1.19	7x7	270	122	HM048SN	1/16	1.59	0.42	0.19	0.49	0.22
HM049	3/64	1.19	1x19	335	152	HM049SN	1/16	1.59	0.55	0.25	0.65	0.29
HM050	3/64	1.19	7x19	270	122	HM050SN	1/16	1.59	0.55	0.25	0.65	0.29
HM054	0.054	1.37	7x49	250	113	HM054SN	1/16	1.59	0.55	0.25	0.65	0.29
HM063	1/16	1.59	1x19	500	227	HM063SN	3/32	2.38	0.85	0.39	1.10	0.50
HM064	1/16	1.59	7x7	480	218	HM064SN	3/32	2.38	0.75	0.34	0.93	0.42
HM065	1/16	1.59	7x19	480	218	HM065SN	3/32	2.38	0.75	0.34	0.93	0.42
HM080	5/64	1.98	7x19	700	318	HM080SN	3/32	2.38	1.42	0.64	1.60	0.73
HM081	5/64	1.98	7x49	550	250	HM081SN	3/32	2.38	1.42	0.64	1.60	0.73
HM082	5/64	1.98	7x7	800	360	HM082SN	3/32	2.38	1.42	0.64	1.60	0.73
HM093	3/32	2.38	1x19	1200	544	HM093SN	1/8	3.18	2.00	0.91	2.20	1.00
HM094	3/32	2.38	7x7	920	417	HM094SN	1/8	3.18	1.60	0.73	1.85	0.84
HM095	3/32	2.38	7x19	920	417	HM095SN	1/8	3.18	1.74	0.79	1.99	0.90
HM096	3/32	2.38	7x49	800	360	HM096SN	1/8	3.18	1.74	0.79	1.99	0.90
HM124	1/8	3.18	1x19	2100	953	HM124SN			3.50	1.59		
HM125	1/8	3.18	7x7	1700	771	HM125SN	3/16	4.76	2.80	1.27	3.60	1.63

**HM Wire International, Inc.**  
 Ph: 330-244-8501 Fax: 330-244-8561  
 www.litz-wire.com info@litz-wire.com www.hmwire.com



## Precision Miniature and Small Cables

### Stainless Steel Cable, Nylon Coated

Uncoated						With Nylon Coating			Approx. Weight per 100 ft.			
Part No.	Nominal Diameter		Constru- ction	Min. Breaking Strength		Part No.	Coating Diameter		Uncoated		Coated	
	in.	mm		lbs	kgs		in.	mm	lbs	kgs	lbs	kgs
<b>HM126</b>	1/8	3.18	7x19	1760	798	<b>HM126SN</b>	3/16	4.76	2.90	1.32	3.62	1.64
<b>HM158</b>	5/32	3.97	7x19	2400	1089	<b>HM158SN</b>	7/32	5.56	4.50	2.04	5.40	2.45
<b>HM188</b>	3/16	4.76	7x19	3700	1678	<b>HM188SN</b>	1/4	6.35	6.50	2.95	8.60	3.90
<b>HM252</b>	1/4	6.35	7x19	6400	2903	<b>HM252SN</b>	5/16	7.94	11.00	4.99	13.50	6.12
<b>HM315</b>	5/16	7.94	7x19	9000	4082	<b>HM315SN</b>	13/32	10.32	17.30	7.85	20.40	9.25
<b>HM375</b>	3/8	9.53	7x19	12000	5443	<b>HM375SN</b>	15/32	11.91	24.30	11.02	28.00	12.70

To be used as a Guideline ONLY!

Copyright ©2012 HM Wire International Inc.

R1. 7/20/2012